



PC Board Layout
Component Side Shown
Dimension Tolerance:±0.05

NOTES : (UNLESS OTHERWISE SPECIFIED)

MATERIAL

- ① HOUSING : HIGH-TEMPERATURE THERMOPLSTIC, UL94V-0
- ② CONTACT : PHOSPHOR BRONZE, Ø0.46mm

SPECIFICATION

- ① VOLTAGE RATING : 125V AC RMS
- ② CURRENT RATING : 1.5AMP @ 25°C
- ③ CONTACT RESISTANCE : 30 MILLIOHMS MAX.
- ④ INSULATION RESISTANCE : 1,000 MEGAOHMS MIN. @ 500V DC
- ⑤ DIELECTRIC VOLTAGE : 1,000VAC RMS 60Hz, 1 MIN.
- ⑥ OPERATING LIFE : 750 CYCLES MIN.
- ⑦ P.C.B. RETENTION RE-SOLDER : 1LB. MIN.
- ⑧ P.C.B. RETENTION POST-SOLDER : 10 LBS. MIN.
- ⑨ STORAGE TEMPERATURE : -40*+85°C
- ⑩ WAVE SOLDERING TEMPERATURE : 250±5°C FOR 5 SECONDS

MATES MODULAR JACK CONFORMING TO TIA-1096-A REGULATIONS.

PRODUCT ORDER INFORMATION

RR66L - 6 * * T00 * P6 - R11NNN *

- PANEL STOP
 P~WITH PANEL STOP
 N~WITHOUT PANEL STOP
- POSITION
 2~6P2C
 4~6P4C
 6~6P6C
- PLATING
 A~Au 0.2~1μ OVERALL
 C~Au 6μ OVERALL
 F~Au 30μ OVERALL
 G~Au 50μ OVERALL
- HOUSING COLOR
 1~BLACK 3~WHITE 4~GREEN
 0~YELLOW#114C 9~COOL GRAY 3U'
 G~GRAY#429C

| | | |
|---|--|--|
| RoHS Directive compliant: 2002/95/EC LEAD FREE PRODUCT | METRIC | Han Electronic |
| | DRAWER Y. TOMITA APPROVER K. KITAGAWA | |
| | DIMENSIONS ARE IN MILLIMETERS TOLERANCES X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 ANGULAR ±0.5° | TITLE REGISTER JACK 6P×C, H=16.30mm VERTICLE, RECEPTACLE |
| | THIRD ANGLE PROJECTION SIZE A4 | PRODUCT NO. RR66L-6**T00*P6-R11NNN* SHEET NO. 1 OF 1 SCALE 1 : 1 |